

E-LynX™ SR

Tactical multi-band, multi-channel soldier SDR
for dismounted forces



- ▶ Secured and powerful SDR platform with 2Tx & 2Rx RF channels
- ▶ Complete NATO frequency coverage: U, L and S bands
- ▶ Extended network coverage with high data rates
- ▶ **Advanced techniques:** Cognitive waveforms with spectrum sensing, unique multi-hop concurrent flooding and MIMO
- ▶ **Robust communication:** Unmatched immunity, information security and GNSS-independent self-synchronization
- ▶ **Versatile operation:** Multiple scenarios including MUM-T
- ▶ **Integrated services:** Simultaneous high-quality voice sessions, IP data, BFT and video in a single network
- ▶ **Intuitive user interface:** Voice menu with multi-language support, wireless PTT and headset



E-LynX™ SR

Multi-role, Multi-waveform

Combat-proven solution providing a dynamic, secured network adaptable to a variety of terrains and missions.

Superior Performance

Seamless communication and situational awareness with superior RF performance and minimal SWaP.

Member of E-LynX™ SDR Family

Delivers advanced multi-domain networking solutions, meeting the complex communication and connectivity needs of modern battlefields across all echelons and operational scenarios.

Technical Specifications

General

Frequency range	225MHz - 3GHz According to antenna selection
Radio presets	100 configurable presets
GNSS	Internal receiver for location report and 1PPS, supporting multiple constellations
Interfaces	Ethernet, USB, analog audio, BT/BLE, external communication bearers (Cellular, Satcom, etc.)
Operation	Keypad and voice feedback
Extensive software tools	Configuration, planning and management, network control, security (including keys generation and loading), network simulation
Mounted Options	2W/20W vehicular adapters

Immune & Secure Communication

ECCM	Robust frequency hopping combined with FEC and interleaver for improved jamming resistance, sense and avoid
Security	<ul style="list-style-type: none"> • COMSEC and TRANSEC utilizing AES-256 • Emergency erase • Secured management via SNMPv3

Power

Power input	9-16 VDC
Power sources	Multiple rechargeable Li-ion battery options

Physical

Dimensions (HxWxD)	123x73x45mm (without battery)
Weight	420g (without battery)

Qualifications

Environmental	MIL-STD-810G
EMC	MIL-STD-461F

Soldier Radio Waveform

Networking	Multi-hop Mobile Ad-Hoc IP Network (MANET) featuring robust routing technologies: concurrent flooding and store & forward, multi-hop, self-forming, self-healing
Services	Simultaneous voice (analog and external VoIP), IP data, IP video and BFT/PLI Multiple voice groups in a single net
Network synchronization	Autonomous, no master station, no single point of failure, no reliance on GNSS receiver or any external signal
Network members	Up to 254 members
Voice groups	<ul style="list-style-type: none"> • Up to 32 simultaneous voice group sessions / Up to 4 voice groups per radio • Dual PTT enables dynamic network hierarchy

Transmitter and Receiver Performance

Output power	2W for UHF band 2 x 1W for L-S bands
Channel bandwidth	Up to 4MHz in UHF Up to 20MHz in L and S bands with MIMO Up to 40MHz for sensing
Frequency stability	+/-0.3ppm
Sensitivity	-106dBm @ 1MHz BW
Spurious suppression	75dB above MDS
Harmonic suppression	HD2/3 > -20dBm, HD4 > -80dBc
Output protection	Open and short-circuit



Elbit Systems C4I and Cyber

2 Hamachshev St., Netanya 4250712, Israel

E-mail: C4icyber.info@elbitsystems.com www.elbitsystems.com

Follow us on